


Ground Clearance
Leg (standard): 130 to 165mm
Castor (Optional): 95 to 115mm
Plinth (Optional): 0mm

Cabinet Dimensions:

	External	Internal
Width (mm):	970	480
Depth (mm):	590	485
Height (mm):	855 to 890 (standard legs) 725 (Plinth) 820 to 840 (castors)	655
Weight (kg):	122	
Capacity (L):	152	
Footprint (m²):	0.57	
Electrical Voltage (V):	220-240	
Electrical Ampere (A):	2	
Electrical Frequency (Hz):	50	
MEPS TEC:	N/A	
Refrigerant:	R134a/R404A	

Dimensional Tolerances + Allow for dimensional tolerance when installing the cabinet(s).	
Linear Dimensions	Single Cabinet Dimensions
Less than 1 metre	+5mm
More than 1 metre	-5mm to +10mm
Length of Multiple Cabinets	
At each joint	At each end wall
+5mm	+15mm
-5mm to +10mm	+15mm



Industries Limited

66 Princess St. PO Box 1091
Christchurch, New Zealand
New Zealand Freephone: 0900 947 5673
Australian Freephone: 1800 121 535
Email: enquiry@skope.co.nz
Website: www.skope.co.nz

Model: GC.1.GSW.r	
Description: One Door (Glass Swing) Glass Chiller, Remote	
Unless Otherwise Specified: Folded Dimension: Overall Linear Tolerances: ± 0.5mm Angular Tolerances: ± 0.5mm Units: Millimeters	Scale: 1 : 20
Copyright © SKOPE Industries Limited	Revision: