


# SKT650NT-A Series

ActiveCore Series, Tropical, 1 Door (Glass), Upright Fridge



Project: \_\_\_\_\_

Item No:



CABINET			
Model ID	SKT650NT-A	SKT650NT-AC	SKT650NT-ACX
Doors	1 × heated, self-closing, reversible, double glazed, single Low-E, lockable, argon filled, toughened safety glass swing door (hinged RH)		
Internal door opening	1 × door openings: 1570mm high × 620mm wide		
Shelves	5 × adjustable height wire shelves: 625mm wide × 470mm deep		
Sign	Sign replacement panel	Illuminated sign	Illuminated sign
Material	Powdercoat galvanized steel or stainless steel interior & exterior		
PERFORMANCE			
Max. ambient temp.	40°C		
Temperature range	1°C to 4°C (adjustable via SKOPE-connect 1°C to 15°C)		
GEMS class	M2		
GEMS energy consumption	8.66 kWh/24h		
GEMS annual running cost	\$949 p.a.(@ \$0.30/kWh)		
ELECTRICAL			
Electrical safety climate class	7		
Interior side lighting	1 × 1400mm, 15W LED	1 × 1400mm, 15W LED	n.a.
Interior shelf lighting	n.a.	n.a.	5 × 605mm, 7W LED
Sign lighting	n.a.	1 × 670mm, 7W LED	1 × 670mm, 7W LED
Power cord	Supplied with 2.3m, 10 Amp plug and lead		
Power supply	220-240 Volts a.c. 50 Hz, single phase supply		
Current draw	4.5 Amps (includes unit 2.6 Amps)		
REFRIGERATION			
Controller	SCS Connect (SKOPE-connect™ compatible)		
Connectivity interface	Bluetooth		
Refrigeration system	Top mounted, integral, removable ActiveCore refrigeration unit (UTHCNI-0010)		
Refrigerant	R290 / 99g (natural refrigerant)		
Nominal capacity	740 Watts		
Heat rejection (Avg/peak)	360 Watts/430 Watts		
Drainage	No plumbing required		

DIMENSIONS		
	External	Internal
Height	2200mm	1570mm
Width	740mm	640mm
Depth	745mm	554mm
Floor area	0.55m <sup>2</sup>	
Weight	170kg	
Gross volume	610L	

\* Depth 695mm excludes removable door handle and door lock bracket

Dimensional tolerances		
Before installing this cabinet allow the following dimensional tolerances:		
Linear dimensions	Overall cabinet dimensions	
Less than 1 metre	±5mm	
More than 1 metre	-5mm to +10mm	
	Length of multiple cabinets	
	At each joint	At each end wall
Less than 1 metre	±5mm	+15mm
More than 1 metre	-5mm to +10mm	+15mm

Ventilation requirements	
Top	300mm
Sides	Not required
Back	Not required
Bottom	Not required

SKOPE Industries Limited reserve the right to alter specifications without notice. Copyright © 2019 SKOPE Industries Limited

**SKOPE INDUSTRIES LIMITED**

Australian Freephone: 1800 121 535, New Zealand Freephone: 0800 947 5673

Email: [skope@skope.com](mailto:skope@skope.com), Website: [www.skope.com](http://www.skope.com)

PSS0600 Rev. 2.1 Aug. 2020

